

RFQ # 30-19 Specifications

SKU	Description	Qty	Unit Price	Subtotal
	Dell PowerEdge R6415	2		
210-ANJO	PowerEdge R6415 Server	2		
384-BBSR	PowerEdge R6415/R7415 Motherboard	2		
461-AAEM	Trusted Platform Module 2.0	2		
321-BDBB	2.5" Chassis with up to 8 Hot Plug Hard Drives	2		
340-BTFM	PowerEdge R6415 Shipping	2		
343-BBGN	PowerEdge R6415 x8 Drive Shipping Material	2		
338-BLLY	AMD EPYC 7281 2.1GHz/2.7GHz, 16C/32T, 32M Cache (155W/170W) DDR4-2400/2666	2		
412-AALH	Standard Heatsink	2		
370-ADNU	2666MT/s RDIMMs	2		
370-AAIP	Performance Optimized	2		
	RAID 1	2		
405-AAEF	PERC H330 RAID Controller, Minicard	2		
634-BLVV	VMware ESXi 6.5 U2 Embedded Image on Flash Media (License Not included)	2		
421-5736	No Media Required	2		
385-BBKT	iDRAC9, Enterprise	2		
528-BBWT	OME Server Configuration Management	2		
379-BCQV	iDRAC Group Manager, Enabled	2		
379-BCSF	iDRAC, Factory Generated Password	2		
330-BBIV	Riser Config 2, 2 x 16 LP	2		
542-BBBP	On-Board LOM	2		
385-BBLQ	IDSDM and Combo Card Reader with 16GB VFlash SD	2		
385-BBCF	Redundant SD Cards Enabled	2		
385-BBKI	64GB microSDHC/SDXC Card	4		
429-ABBF	No Internal Optical Drive for x4 and x8 HDD Chassis	2		
450-AGZB	Dual, Hot-plug, Redundant Power Supply (1+1), 550W	2		
325-BCHH	Standard Bezel	2		
350-BBMD	Dell EMC Luggage Tag	2		
350-BBKQ	Quick Sync 2 (At-the-box mgmt)	2		
384-BBBL	Performance BIOS Settings	2		
800-BBDM	UEFI BIOS Boot Mode with GPT Partition	2		

RFQ # 30-19 Specifications

SKU	Description	Qty	Unit Price	Subtotal
770-BBBC	ReadyRails Sliding Rails Without Cable Management Arm	2		
631-AACK	No Systems Documentation, No OpenManage DVD Kit	2		
332-1286	US Order	2		
816-0779	Dell Hardware Limited Warranty Plus On-Site Service	2		
816-0792	ProSupport: Next Business Day On-Site Service After Problem Diagnosis, 5 Years	2		
816-0813	ProSupport: 7x24 HW/SW Technical Support and Assistance, 5 Years	2		
989-3439	Thank you choosing Dell ProSupport. For tech support, visit	2		
900-9997	On-Site Installation Declined	2		
370-ADNF	32GB RDIMM 2666MT/S Dual Rank	16		
400-BCOM	1.92TB SSD SAS Mixed use 12Gbps 512e 2.5in Hot-Plug PM5-V Drive, 3 DWPD, 10512	4		
540-BBVI	Broadcom 57412 Dual Port 10GbE SFP+ Adapter, PCIe Low Profile	4		
450-AALV	NEMA 5-15P to C13 Wall Plug, 125 Volt, 15 AMP, 10 Feet (3m), Power Cord, North	4		

Note:

- 370-ADNF Can be substituted with 64GB (or higher) RAM modules.
The total memory for each server has to be a minimum of 256GB.
- 338-BLLY Can be any AMD EPYC CPU that is at least 16c/32t and minimum 2.1GHz
- 540-BBVI Can be any 10Gbs (or faster) network card that provides 2 ports and is compatible with VMware and Windows server
- 400-BCOM This can be substituted with another or better SSD hard drive with the same usage, size, speed, lifespan and size.